



DIAMOND
Committed to supply
Quality Product

General Purpose Polystyrene.
Injection Grade

DESCRIPTION:

DIAMOND GP-560 is a General Purposes Polystyrene having excellent clarity and gloss. It is available in Blue tint and has good dimensional stability at High temperature.

GP-560 **Excellent clarity, Blue Tinted, Good Flow.**

SPECIFICATIONS:

GRADE	TENSILE PROPERTIES ASTM D-638		IMPACT PROPERTIES ASTM D-256		FLEXURAL PROPERTY ASTM D-790	THERMAL PROPERTY		OTHER PROPERTIES	
	Tensile	Elongation	Izod Impact Strength	Gardner Falling Dart		ASTM D-648	ASTM D-1525		
	Kgs/Cm ²	%	Kgf-Cm/Cm	Cm-Kg		Kgs/Cm ²	HDT	Vicat Softening Temp.	Melt Flow Index
GP- 560	380	1	1.6	--	650	85	90	Gm/10mins.	-

Remarks: The data intended as general guide only and do not represent results that may be obtained elsewhere.

CHARACTERISTICS:

Blue Tinted, Excellent Clarity, Good Flow, Low Volatility (below 1000 ppm).

APPLICATIONS:

GP-560:

House ware, Containers, Toys and Lamp-shield and thin wall applications.

PAK PETROCHEMICAL INDUSTRIES (PVT) LTD.

Polymer House, Survey # 136, Main National Highway,
Karachi.
Tel: 92-21-5019701-4, Fax: 92-21-5018552-3
Email: info@polystyrene.com.pk
Web : www.polystyrene.com.pk



ISO 9001 CERTIFIED